



PRODUCT-DETAILS

UPS PowerValue 11T G2 3 kVA B

UPS PowerValue 11T G2 3 kVA B



General Information	
Extended Product Type	UPS PowerValue 11T G2 3 kVA B
Product ID	4NWP100162R0001
EAN	7640169261923
Catalog Description	UPS PowerValue 11T G2 3 kVA B
Long Description	VFI online double conversion;2700W;9min;RS232;USB;mini COM slot

Environmental	
Environmental Information	No declaration needed

Material Compliance	
Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
REACH Declaration	4NWD004620
RoHS Information	4NWD004828

RoHS Status	Following EU Directive 2011/65/EU
SCIP	6bbb3694-0f69-48ab-acd6-8dd73d820ded Switzerland (CH)
Simplified SCIP	bc52f4bd-a75e-4012-8581-e3bdb78d09df Germany (DE) 5e520238-e054-4c7c-a5b9-6649692b2f1e Germany (DE) b8dc0e89-b0ae-4daf-816a-ff8d2d217f87 Denmark (DK) 62552071-e935-4f2a-9bec-060082f8926e Sweden (SE) dd27df88-b4e0-42ee-a061-655d07c9f242 Belgium (BE) 5ec09eb1-d007-4ce9-a345-ebfc9d42ccf9 Germany (DE) 02da048d-2f16-4081-8bec-a330a63e0a65 Estonia (EE) 994b81ad-33a7-4e3e-bb68-eddb7322c18e Germany (DE) 12ee1b5b-3af8-43bd-b672-a10cc4ee7910 Greece (GR) 5c4fa7ed-5f69-41be-9c73-1e1d81eabb53 Norway (NO) a32037e0-4e52-44ed-9380-d1442d3062bb Poland (PL) a4e606f5-1cd1-4a89-a43c-8670f74a77c7 Finland (FI) df321ff5-c466-4b6f-9d27-1520c393d3f2 Sweden (SE) 5a082374-bd0a-4fd4-98db-2bbc7dc98a26 Portugal (PT) e1b5ab9e-621f-4489-bd93-d9937c2568b0 France (FR) 151181b2-d449-4498-9fa4-e2fbef57f484 Hungary (HU) 42a11e85-fba3-4ae3-97e6-a0830f514ecf Poland (PL) 11da99ae-84d7-44df-9cae-71a464b2f4e7 Bulgaria (BG) b6a12507-2cc4-48d9-9de7-8faa3f117d26 Croatia (HR) 85ad13f2-14f4-47a3-8a55-9787a9ac55ad Czech Republic (CZ) 910ea1b7-259f-4b69-ab81-95e4f67b12dd Germany (DE) 64e20eba-e4a7-4c3d-bf39-cca1fbb33661 France (FR) 875ecc11-e0e4-4366-b04d-ad62d2136201 Hungary (HU) 90e6199d-2e2c-4933-891b-6e8423a4a4cb Netherlands (NL) 3088ee64-3efd-4093-baf9-95c1f9ad27ed Belgium (BE) 0815ee1d-156f-4c55-9e89-9e07e2bb01ea Spain (ES) 9e0ecf28-24ec-4770-86fd-b58408cd784f Poland (PL)

Technical

Input Voltage (U _{in})	220 V 230 V 240 V
Input Voltage Type	AC
Rated Frequency (f)	Primary 50 Hz Primary 60 Hz Secondary 50 Hz Secondary 60 Hz
Apparent Power Output	3000 V·A
Rated Output Power	2700 W
Communication Interface	USB, RS-232
Number of Phases	Primary - 1 Secondary - 1
Number of Outputs	C13 Connection 4 C19 Connection 1
Connection Type	IEC C20
Options Provided	Auto shut down function Potential free switch contact Network-management
Battery Chemical Composition	Lead-Acid
Battery Type	Portable
Battery Weight	2.5 kg
Number of Batteries	4

Dimensions

Product Net Width	190 mm
Product Net Height	327 mm

Product Net Depth / Length	399 mm
Product Net Weight	22.2 kg

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	324 mm
Package Level 1 Height	464 mm
Package Level 1 Depth / Length	500 mm
Package Level 1 Gross Weight	24.6 kg
Package Level 1 EAN	7640169261923

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85044000
E-Number (Finland)	8408612
E-Number (Norway)	6609404
E-Number (Sweden)	5257249
Country of Origin	China (CN)

Certificates and Declarations

Declaration of Conformity - CCC	No certification needed
Declaration of Conformity - CE	4NWD004828

Popular Downloads

Data Sheet, Technical Information	4NWD003883_EN
Instructions and Manuals	4NWD003883_EN

Classifications

ETIM 7	EC000382 - UPS
ETIM 8	EC000382 - UPS
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Business
CN8	85044000
eClass	V11.1 : 27040690
Object Classification Code	G

Categories

UPS, Power Conditioning and Power Distribution → UPS → Single-Phase UPS → PowerValue 11 T G2 IEC 230V

